

PRO ECO FREEDOM TO SAVE WITH ABSOLUTE COMFORT.



PRO ECO is the best solution for the user who wants a product able to guarantee the maximum saving and at the same time maximum performance and maximum safety. Thanks to ECO technology, Nanomix+Best system and the ABS package, PRO ECO allows the user to save up to 10% energy consumption per year, to produce up to 40 lt. more of water at 40°C and to offer the maximum use safety.

There is a new design for PRO ECO: the Smart thermometer is in the frontal led control panel.

**Exclusive
design**

+10%
ENERGY SAVING

PRO ECO



COMFORT

- Digital temperature regulation
- High precision NTC temperature sensors

EFFICIENCY&ENERGY SAVING

- Eco function
- Ecological polyurethane insulation

QUALITY

- Titanium glasslined inner tank tested at 16 bar
- Oversize magnesium anode
- 5-bolts flange
- Pressure safety valve tested at 8 bar
- ABS safety package

DESIGN

- Led display
- Exclusive Italian design
- Wall-hung



علامة الجودة الإماراتية
Emirates Quality Mark



**comfort
and saving**

TECHNICAL DATA





		PRO ECO 50 V	PRO ECO 80 V	PRO ECO 100 V	PRO ECO 50 H	PRO ECO 80 H	PRO ECO 100 H
Capacity	l	50	80	100	50	80	100
Installation	V	V	V	V	H	H	H
Size		Regular	Regular	Regular	Regular	Regular	Regular
Power	kW	1,5	1,5	1,5	1,2	1,5	1,5
Voltage	V	230	230	230	230	230	230
Heating time ($\Delta T=45^{\circ}\text{C}$)	h,min	1:50'	2:56'	3:40'	2:17'	2:56'	3:40'
Heat dispersion at 65°C	kWh/24h	0,96	1,22	1,39	0,96	1,48	1,65
Max working pressure	bar	8	8	8	8	8	8
Max working temperature	$^{\circ}\text{C}$	80	80	80	80	80	80
Weight	kg	16,5	22	25,5	16,5	22	25,5
Class	IP	IPX3	IPX3	IPX3	IPX1	IPX1	IPX1

OVERALL DIMENSIONS

a	mm	550	758	913	550	758	913
b	mm	398	603	758	-	-	-
c	mm	-	-	-	155	174	177
d	mm	-	-	-	160	335	487

CODE

3200417	3200418	3200419	3200420	3200421	3200422
---------	---------	---------	---------	---------	---------



LEGEND

- E** Cold water inlet G 1/2"
- U** Hot water outlet G 1/2"