

ELECTRIC WATER HEATER – SHAPE ECO

TECHNICAL SPECIFICATIONS

Wall hung electric storage water heater - Energy efficiency and style together

Features:

- Innovative design
- High precision NTC Temperature sensors
- Easy and fast reset
- 5 Bolts flange
- Thick thermal insulation
- Oversize magnesium anode
- Maximum protection: up to IP25D
- High efficiency expanded polyurethane insulation
- Pressure safety valve tested at 8 bar
- Product tested to the highest quality standards
- Titanium glass-lined inner tank tested at 16 bar
- Maximum comfort

Capacity	50 L VERTICAL	80 L VERTICAL	100 L VERTICAL
Power (kW)	1.8	1.8	1.8
Voltage (V)	230	230	230
Heating time - 45 °C (h.mins)	1.32	2.27	3.03
Max. working temp (°C)	80	80	80
Heat dispersion at 65°C (kWh/24h)	0.8	0.94	1.08
Max. working pressure (bars)	8	8	8
Net weight (kg)	19	23.5	27
Protection (IP)	X4	X4	X4
Dimensions (mm)	570 x 379 x 191	775 x 584 x 191	927 x 736 x 191
No. of simultaneously users	2 (Sink/Washbasin & Shower)	3 (Sink, Washbasin & Shower) or (Washbasin, Bathtub & Shower)	3/4 (Sink, Washbasin, Bathtub & Shower)



TITANIUM PLUS
A new technology which uses titanium enamelling for greater protection.



ITALIAN DESIGN
Guarantee of quality



POLYURETHANE INSULATION
CFC free insulation material according to the latest environment requirements.



ECO
Reduction of consumption thanks to ECO function.



ABS
Total electronic safety package for a total safety comfort.



NANOMIX + BEST
Much more quantity of hot water and top performance thanks to the BEST Technology and Nanomix.



DISPLAY ECO
Frontal led control panel with smart thermometer