

SuperG R

ENAMELLED
STEEL TANKPOLYURETHANE
INSULATIONTEMPERATURE
REGULATION

COMFORT

- External temperature regulation

EFFICIENCY&ENERGY SAVING

- Double layer exclusive glasslining

QUALITY

- High thickness steel tank tested at 16 atm
- Oversized magnesium anode
- Original Ariston thermostat with built-in safety device
- External thermometer
- Pressure safety valve rated at 8 bar

DESIGN

- Wall-hung



علامة الجودة الإماراتية
Emirates Quality Mark



temperature regulation

TECHNICAL DATA

		SuperG R 50V	SuperG R 80V	SuperG R 100V	SuperG R 50H	SuperG R 80H	SuperG R 100H
Capacity	l	50	80	100	50	80	100
Power	kW	1,5	1,5	1,5	1,2	1,5	1,5
Voltage	V	230	230	230	230	230	230
Heating time ($\Delta T = 45^{\circ}\text{C}$)	h:m	1,56	3,06	3,52	2,25	3,06	3,52
Max. Working Temp.	$^{\circ}\text{C}$	75	75	75	75	75	75
Heat dispersion	kWh/24h	0,96	1,22	1,39	1,02	1,48	1,65
Max. Working Pressure	bar	8	8	8	8	8	8
Weight	kg	17	23	25	17	23	25
Protection	IP	IPX3	IPX3	IPX3	IPX1	IPX1	IPX1

OVERALL DIMENSIONS

a	mm	553	758	913	553	758	913
b	mm	398	603	758	-	-	-
c	mm	-	-	-	155	174	177
d	mm	-	-	-	160	335	487
e	mm	155	155	155	-	-	-
f	mm	165	165	165	-	-	-

CODE

3605437 3605438 3605439 3605440 3605441 3605442

LEGEND

- E** Cold water inlet G 1/2"
U Hot water outlet G 1/2"