



Wall-hung electric storage water heater
can be installed over or under the sink



TITANIUM



POLYURETHANE
INSULATION



TEMPERATURE
REGULATION



ANTI-FREEZE

- TITANIUM GLASSLINED INNER TANK AT 850°C
- OVERSIZED MAGNESIUM ANODE
- HIGH PRECISION REGULATION
- HIGH SENSITIVITY THERMOSTAT
- REDUCED RESTORE TIME
- MAXIMUM PROTECTION: UP TO IP25D

super
compact

Technical data - Overall dimensions

		SHAPE									
		10 R/5	10 ST R/5	15 R/5	15 ST R/5	30 R/5					
Capacity	l	10	10	15	15	30		a mm	357	357	447
Power	W	1200	1200	1200	1200	1500		b mm	261	308	370
Voltage	V	230	230	230	230	230		c mm	357	357	447
Heating time ($\Delta T = 45^\circ\text{C}$)	h, min.	0,29	0,29	0,44	0,44	1,10		d mm	92	78	114
Max. Working Temp.	$^\circ\text{C}$	80	80	80	80	80					
Heat dispersion 65°C	kWh/24h	0,43	0,55	0,53	0,65	0,61					
Max. Working Pressure	bar	8	8	8	8	8					
Weight (net)	kg	6,6	6,6	7,4	7,4	12,8					
Protection	IP	IPX4	IPX4	IPX4	IPX4	IPX4					

ST = undersink





SHAPE 10 R/5
3100226

SHAPE 10 ST R/5
3100227

SHAPE 15 R/5
3100228

SHAPE 15 ST R/5
3100255

SHAPE 30 R/5
3100229



legend

E cold water inlet G 1/2"

U hot water outlet G 1/2"