

ELECTRIC WATER HEATER – SHAPE SMALL

TECHNICAL SPECIFICATIONS

Super compact water heater - Wall-hung electric storage water heater can be installed over or under the sink

Features:

- Titanium glass-lined inner tank at 850 °C
- Oversized magnesium anode
- High precision regulation
- High-sensitivity thermostat
- Reduced restore time
- Maximum protection: up to IP25D

Capacity	10 L Undersink	10 L Oversink	15 L Oversink	30 L Oversink
Power (W)	1200	1200	1200	1500
Voltage (V)	230	230	230	230
Heating time - 45 °C (h.mins)	0.29	0.29	0.44	1.10
Max. working temp (°C)	80	80	80	80
Heat dispersion at 65°C (kWh/24h)	0.55	0.43	0.53	0.61
Max. working pressure (bars)	8	8	8	8
Net weight (kg)	6.6	6.6	7.4	12.8
Protection (IP)	X4	X4	X4	X4
Dimensions (mm)	357 x 261 x 357 x 92		357 x 308 x 357 x 78	447x 370 x 447 x 114
No. of simultaneously users	1 (Sink or Washbasin or Shower)			



TITANIUM PLUS
A new technology which uses titanium enamelling for greater protection.



EXTERNAL TEMPERATURE REGULATION
Easy to set a temperature desired.



POLYURETHANE INSULATION
CFC free insulation material according to the latest environment requirements.



ANTI-FREEZE
The water heater is protected against extremely low temperature.



TBST Thermostat
The TBST Thermostat combines functional and safety devices allowing much more precise and reliable performances. Faster reaction time allows a faster hot water recovery.